



■ Palletizer - PACKOMAT

- Bilateral series order
- Adjustable feet to stabilize the machine
- Approximately 25 m of netting per pallet
- Quick and tool-free drum attachment
- Quick and tool-free spool change
- Standard three-point hitch
- Adjustable column output speed to accommodate all net heights
- Standard manual orientation. Hydraulic option



PACKOMAT



Dual palletizer



VERSIONS		SINGLE DRUM <i>(Supplied without drum)</i>		DOUBLE DRUM <i>(Supplied without drum)</i>	
		PAL100000	PAL100001	PAL100100	PAL100101
Power supply		PTO tractor	Elec. 400 V	PTO tractor	Elec. 400 V
Maximum rotational speed of the PTO shaft (rpm)		360	-	360	-
Length (cm)		235			
Width (cm)		130		343	
Transport height (cm)		253			
Maximum working height (cm)		433			
Maximum hydraulic circuit pressure (bar)		220			
Lifting cylinder stroke (cm)		170			
Net weight (kg)		580	590	670	680
ACCESSORIES	Hydraulic orientation option <i>(only available on double model)</i>			PAL110002	
	Expander for palletizer <i>(conversion from single machine to double)</i>			PAL110003	
	Netting for palletizer <i>(Height = 60 cm / Length = 1800 m)</i>			FIL000110	

VERSIONS	ROUND DRUM	RECTANGLE DRUM
Dimensions (H x Ø cm)	140 x 117	-
Dimensions (H x L x W cm)	-	140 x 120 x 80
Volume (m³)	1,50	1,25
Weight (kg)	130	125

